PERFORMER G







Refrigerated Showcase for Gastronomy Applications

Tempered front double glass, upward opening | double glass sides | temperated upper service glass | brilliant aluminum profiles | operator side closure with plexiglass panels | tank insulated with ecological polyurethane and covered with stainless steel | ventilated refrigeration | electronic control unit and digital temperature reader flush with the surface | display trays in polished steel | worktop in polished steel with servo-assisted lifting system of the worktop and the evaporator unit to guarantee perfect cleaning of the tank bottom | supporting frame in galvanized steel with height-adjustable stainless steel feet
















Technical







> Ventilated

R452A

Hermetic

Automatic/electrical

120 V / 1 ph / 60 Hz

∏= 39.2 °F

Data Sheet *Measurements are subject to revisions/updates, please refer to manufacturer's drawings at order confirmation *Crate weight only



Model Code	Dimensions L x D x H Inches	Weight Lbs	Max Pwr. Consumpion W / A	Avg Operating Consumption KW/H	Cooling Power/Expansion BTU / °F	GAS Type
PFRG115I (+PANELS)	45 ¹ /4x45 ³ /8x45 ³ /8 52 ³ /8x52 ⁷ /16x56 ³ /4	441 P 287	600/4,5	0,45	1740 / 14	R452A
PFRG165 (+PANELS)	64 ¹⁵ /16x45 ³ /8x45 ³ /8 72 ¹ /16x52 ⁷ /16x56 ³ /4	639 397	800/5,5	0,6	2286 / 14	R452A
PFRG215 (+PANELS)	84 ⁵ /8x45 ³ /8x45 ³ /8 91 ³ /4x52 ⁷ /16x56 ³ /4	728 ③ 496	1200/8,0	0,85	3037 / 14	R452A
PFRGAP90	63 ⁵ /8×63 ⁵ /8×45 ³ /8	750	1300/8,5	0,9	3207 / 14	R452A

Optionals:



CIV65-68 Intermediate fix shelf



CIV57 Glass divider for display area



CIT46 Remote assistance Epoxy painted



PVP00-003 profiles

70 11/16x70 11/16x56 3/4



CIV01 s/s plate for scale



MB324/325 TGL01 Polyethylene cutting s/s esposition step Custom worktop board



CISF65-77



DPV01 10mm lowering around sinks



(+PANELS)

CIAM Spa Viale dei Pini, 9 - 06081 Petrignano di Assisi - PG, Italy T +39 075 80161 - info@ciamgroup.it - www.ciamweb.it









